



The Last Pour Point Depressant You Will Ever Need!

SubZero is a multifunctional middle distillate fuel additive. It functions as a wax modifier to improve low temperature operability of diesel fuel.

SubZero will help provide the following performance benefits:

- ✓ Lowers Cold Filter Plugging Point
- ✓ Lowers Pour Point
- ✓ Prevents fuel gelling in low temperatures
- ✓ Disperses wax during extended engine shutdowns in cold climates
- ✓ Aids against fuel filter icing
- ✓ Water dispersant to help safely remove water on a gradual basis
- ✓ Caustic resistant corrosion inhibitor
- ✓ Fully synthetic ester lubricity improver

Personal Safety, First Aid and Storage and Handling

See the Material Safety Data Sheet for product specific information. **SubZero** may be continuously or batch blended into diesel fuel as a concentrate or as a stock solution. Proper blending and handling procedures must be followed due to the nature of all low temperature operability additives. Blend the additive with the fuel at temperatures at least 10°F above the cloud point of the fuel. Ensure the additive is at or above minimum handling temperatures to avoid potential performance issues. Verify that the additive is completely dissolved into the fuel.

Material Compatibility

SubZero is compatible with the following materials of construction: mild steel, aluminum, 304 stainless steel, 316 stainless steel, Teflon, and Viton. Do not use with ethylene, propylene, neoprene, Buna-N, or natural rubber. Copper, brass, or bronze (yellow metals) should not be used with neat additive.



Typical Properties

Appearance	amber liquid
Specific Gravity, 60/60°F (15°C)	0.904
Density, lb./gal, 60°F, (15.6°C).	7.52
Flash Point, PMCC, °F (°C).	166 (74.4)
Pour Point, °F (°C).	-22 (-30)
Viscosity, cSt @ 100°F (37.8°C)	4
68°F (20°C).	6
32°F (0°C).	12
0°F (-17.8°C).	30

Recommended Treat Rate

1 pint : 275 gallons
EPA Maximum Treat Rate: 2500 mg/L



For more information, please contact Global Marketing Department at (800) 685-7222 www.globalp.com

Call your local FW Webb to place an order or visit www.fwwebb.com for a list of locations. Please reference item #472451.